

Performance

- Adopting LONGi HPBC solar cells with zero-busbar, offering a sleek appearance and higher efficiency.
- Stable output in low light and partial shade conditions.
- Intergraded bypass diodes for each cell is not only fireproof ensuring the continuous output even part of the cells are damaged.
- Original module technology increased the efficiency by 3% compared to traditional full black modules.
- Ideal for RVs, yacht, balcony and BIPV applications.

Manufacturing

- El-Testing before packing
- Comprehensive module power testing

Warranty

- 5 years Manufacturer Warranty
- Warranty on Electrical Performan: 10 years 90% , 25 years 80% of power ourput



Electrical Parameters (Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C)

Nominal Power	240W
Cell Type	LONGi HPBC Mono-crystalline
Cell Efficiency	>25%
Maximum Power Current (Impp)	11.82A
Maximum Power Voltage (Vmpp)	20.32V
Open-circuit Voltage (Voc)	23.20V
Short-circuit Current (Isc)	12.53A

Operating Parameters

Operating temperature range	-40°C ~ +85°C
Output Tolerance	0~+3%
Max. System Voltage	500V
Max. Series Fuse Rating	20A

Mechanical Parameters

Junction box rating	IP67
Output Cable	700mm/2.5mm ² /MC4
Frame	Anodized aluminum alloy frame
Glass	Single glass, 3.2mm coated tempered glass
Diode	√

Packaging

Module Dimensions	1520*760*30mm
Module Weight	11.8/13.3kg
Package	Single Package
Pieces per Pallet	29 pcs
Gross Weight per Pallet	410kg
Pallet Dimensions	1540*1100*920mm

SOLMAX NEW ENERGY B.V.

Address: defensiedok 18, 3433 KL Nieuwegein, Utrecht ,NL
 TEL:0031-307855708
 Whatsapp:031-620074476
 Email:info@solarfam.nl

